SPECIFICATION Of 2000 Lumens

All In One Solar Street Light

1. 3 lighting modes with PIR motion sensor

2. ALS2.0 + VFT + TCS Technology for All Night Lighting even in Cloudy or

Rainy Day.

Application: Street /Roadway /pathway /Parking Lot /Private/road /Sidewalk /Public square





SPECIFICATIONS

Model No.	SSL-32
Lumens	2000lm
LED quantity	20pcs
Power of solar panel	18W
Battery Spec	148WH
IP	65
IK	10
Charging time	10 hours
Lighting time	7-10 days
Discharing temperature	-20℃~65℃
Charging temperature	0℃~55℃
Switch light sensor	≥50 Lux,off
	≤ 10 Lux,on
Light modes	3 lighting modes + ODM
Beam angle	137.2 * 78.3°
Material	Aluminum alloy
Warranty	3 years

















WORKING PROCESS INSTRUCTIONS

1. Power Li-ion battery, support 1500 cycles

2. Battery pack outside the lamp, very convenient to replace and maintenance.

3. 3 colors indicators for 3 lighting modes

Red: 30% brightness + PIR100% brightness

Green: 5H 100% brightness + 5H 25%brightness,70% brightness till dawn

Orange: 70% constant brightness all night










Switch



Battery


RECOMMEND DATA



New technology:


ALS (adaptive lighting system): When meet bad weather lack of enough sun charge, the system will do Smart timely calculation for the remaining battery capacity and give max output efficiency use to prolong Lighting time.

TCS (Temperature control system) when temperature over 65 $^{\circ}$ C.TCS will cut off charging system to Protect battery, when below 65 $^{\circ}$ C, charging system will continue to work automatically





DIALUX road simulation map Pole diameter: 60mm

PRODUCT SIZE



PRODUCT PACKAGING





Lamp Net Weight 6.25 KG Lamp Net Weight

1.335 KG